MATERIAL SAFETY DATA SHEET

Paints

prepared 12/29/99

HAZARDS IDENTIFICATION (ANSI Section 3)

Primary route(s) of exposure Inhalation, skin contact, eye contact, ingestion

Effects of overexposure :

Inhalation · Irritation of respiratory tract Prolonged inhalation may lead to mucous membrane irritation, drowsiness, dizziness and or lightheadedness, headache, nausea, coughing, central nervous system depression, difficulty of breathing, kidney damage

Skin contact Irritation of skin Prolonged or repeated contact can cause dermatitis, defatting Possible sensitization to skin

Eye contact . Irritation of eyes Prolonged or repeated contact can cause conjunctivitis

Ingestion : Ingestion may cause mouth and throat irritation, dizziness and/or lightheadedness, headache, vomiting, gastro-intestinal disturbances, severe abdominal pain, apathy, central nervous system depression, respiratory problems, intoxication, kidney damage, pulmonary edema, loss of consciousness, acute poisoning, respiratory failure, cardiac failure, brain damage

Medical conditions aggravated by exposure Eye, skin, respiratory disorders asthma-like conditions kidney disorders

FIRST-AID MEASURES (ANSI Section 4)

Inhalation : Remove to fresh air Restore and support continued breathing Get emergency medical attention Have trained person give oxygen if necessary Get medical help for any breathing difficulty Remove to fresh air if inhalation causes eye watering, headaches, dizziness, or other discomfort

Skin contact Flush from skin with water Then wash thoroughly with soap and water Remove contaminated clothing Wash contaminated clothing before re-use

Eye contact . Flush immediately with large amounts of water, especially under lids for at least 15 minutes If irritation or other effects persist, obtain medical treatment

Ingestion If swallowed, obtain medical treatment immediately

FIRE-FIGHTING MEASURES (ANSI Section 5)

Fire extinguishing media : Dry chemical or foam water fog Carbon dioxide Closed containers may burst if exposed to extreme heat or fire Easily ignited if allowed to dry In closed tanks, water or foam may cause frothing or eruption

Fire fighting procedures · Water may be used to cool and protect exposed containers Firefighters should use full protective clothing, eye protection, and self-contained breathing apparatus

Hazardous decomposition or combustion products Carbon monoxide, carbon dioxide, monomer vapors, oxygen, styrene Acrylic monomers

ACCIDENTAL RELEASE MEASURES (ANSI Section 6)

Steps to be taken in case material is released or spilled Comply with all applicable health and environmental regulations Eliminate all sources of ignition Ventilate area Spills may be collected with absorbent materials Evacuate all unnecessary personnel Place collected material in proper container Small spills - use absorbent to pick up residue and dispose of properly

HANDLING AND STORAGE (ANSI Section 7)

Handling and storage Store below 100f (38c) Keep away from heat, sparks and open flame Keep from freezing

Other precautions Use only with adequate ventilation Do not take internally Keep out of reach of children Avoid contact with skin and eyes, and breathing of vapors Wash hands thoroughly after handling, especially before eating or smoking Keep containers tightly closed and upright when not in use Avoid conditions which result in formation of inhalable particles such as spraying or abrading (sanding) painted surfaces If such conditions cannot be avoided, use appropriate respiratory protection as directed under exposure controls/personal protection

EXPOSURE CONTROLS/PERSONAL PROTECTION (ANSI Section 8)

Respiratory protection · Control environmental concentrations below applicable exposure standards when using this material When respiratory protection is determined to be necessary, use a NIOSH/MSHA (Canadian z94 4) Approved elastomeric sealing surface facepiece respirator outfitted with organic vapor cartridges and paint spray (dust/mist) prefilters Determine the proper level of protection by conducting appropriate air monitoring Consult 29CFR1910 134 For selection of respirators (Canadian z94 4)

Ventilation Provide dilution ventilation or local exhaust to prevent build-up of vapors

Personal protective equipment : Eye wash, safety shower, safety glasses or goggles Impervious gloves, impervious clothing

STABILITY AND REACTIVITY (ANSI Section 10)

Under normal conditions · Stable see section 5 fire fighting measures

Materials to avoid : Oxidizers, acids

Conditions to avoid Elevated temperatures, contact with oxidizing agent, freezing, sparks, open flame

Hazardous polymerization Will not occur

TOXICOLOGICAL INFORMATION (ANSI Section 11)

Supplemental health information No additional effects are anticipated

Carcinogenicity · No carcinogenic effects are anticipated

Reproductive effects No reproductive effects are anticipated

Mutagenicity · No mutagenic effects are anticipated

Teratogenicity Some laboratory test results have shown ethylene glycol to be an animal teratogen

ECOLOGICAL INFORMATION (ANSI Section 12)

No ecological testing has been done by ICI paints on this product as a whole

DISPOSAL CONSIDERATIONS (ANSI Section 13)

Waste disposal Dispose in accordance with all applicable regulations Avoid discharge to natural waters

REGULATORY INFORMATION (ANSI Section 15)

As of the date of this MSDS, all of the components in this product are listed (or are otherwise exempt from listing) on the TSCA inventory This product has been classified in accordance with the hazard criteria of the CPR (controlled products regulations) and the MSDS contains all the information required by the CPR

ICI Paints North America 925 Euclid Avenue Cleveland Ohio 44115 EMERGENCY TELEPHONE NO (800) 545-2643

ULTRA-HIDE EXTERIOR ACRYLIC SATIN

GL2412

Physical Data (ANSI Sections 1, 9, and 14)

Product Code	Description	Wt. / Gal.	VOC gr. / ltr	% Volatile by Volume	Flash Point	Boiling Range	HMIS	DOT, proper shipping name
GL2412-0100	glidden ultra-hide durus acrylic satin exterior, white	10 23	133 66	68 45	none	212-212	*210	paint ** protect from freezing **
GL2412-0110	glidden ultra-hide durus acrylic satin exterior white tint base	10 30	131 99	68 16	none	212-212	*210	paint ** protect from freezing **
GL2412-0300	glidden ultra-hide durus acrylic satin exterior, intermediate tint base	9 56	170 19	73 89	none	212-477	*210	paint ** protect from freezing **
GL2412-0400	glidden ultra-hide durus acrylic satin exterior, deep tint base	9 36	152 44	69 90	none	212-477	*210	paint

Ingredients Product Codes with % by Weight (ANSI Section 2)

Chemical Name	Common Name	CAS No	GL2412-0100	GL2412-0110	GL2412-0300	GL2412-0400
1,2-ethanediol	ethylene glycol	107-21-1	1-5	1-5	1-5	1-5
titanium oxide	titanium dioxide	13463-67-7	10-20	10-20	5-10	1-5
propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol	texanol	25265-77-4	1-5	1-5	1-5	1-5
2-propenoic acid, 2-methyl-, methyl ester, polymer with butyl 2-propenoate	acrylic polymer	25852-37-3	10-20	10-20	10-20	
nepheline syenite	feldspar-type minerals	37244-96-5	1-5	1-5	5-10	10-20
silica	amorphous silica	7631-86-9			1-5	
water	water	7732-18-5	50-60	50-60	50-60	50-60
acrylic resin	acrylic resin	Sup Conf				20-30

Chemical Hazard Data (ANSI Sections 2, 8, 11, and 15)

		ACGIH-TLV				OSHA-PEL				S R.	S2	S3	CC					
Common Name	CAS No	8-Hour TWA	STEL	C	S	8-Hour TWA	STEL	C	S	Std.				H	M	N	I	O
ethylene glycol	107-21-1	not est	not est	100 mg/m3	not est	not est	not est	not est	not est	not est	n	y	y	y	n	n	n	n
titanium dioxide	13463-67-7	10 mg/m3	not est	not est	not est	10 mg/m3	not est	not est	not est	not est	n	n	n	n	y	n	n	n
texanol	25265-77-4	not est	not est	not est	not est	not est	not est	not est	not est	not est	n	n	n	n	n	n	n	n
feldspar-type minerals	37244-96-5	5 mg/m3	not est	not est	not est	not est	not est	not est	not est	not est	n	n	n	n	n	n	n	n
amorphous silica	7631-86-9	10 mg/m3	not est	not est	not est	6 mg/m3	not est	not est	not est	not est	n	n	n	n	n	n	n	n

Footnotes

C=Ceiling - Concentration that should not be exceeded even instantaneously

S=Skin - Additional exposure, over and above airborn exposure may result from skin absorption

n/a=not applicable
not est=not established
CC=CERCLA Chemical

ppm=parts per million
mg/m3=milligrams per cubic meter
Sup Conf=Supplier Confidential

S2=Sara Section 302 EHS
S3=Sara Section 313 Chemical
S R Std =Supplier Recommended Standard

H=Hazardous Air Pollutant M=Manne Pollutant
P=Pollutant S=Severe Pollutant
Carcinogenicity Listed By
N=NTP I=IARC O=OSHA, y yes n=no